

SPMP LED



η_{ef} (lm/W)
71-100

Bruksområde

- Utenpåliggende armatur for tak/vegg.

Armatur

- Stål hvitlakkert, RAL 9003.

Optikk

- Opal eller mikrop Prismatisk avdekning.

Bestykning

- LED Osram/Samsung.
- 3000° eller 4000° Kelvin.
- CRI 80 standard (kan leveres med CRI 90).



Varianter

- Digital dimming (DALI).



Art. nr.	W	Lumen	Kelvin	Ø	X	Y	C	
429215	14	1100	3000	190	120	140	41	Prism.
429224	22	1800	3000	190	120	140	41	Prism.
429216	28	2600	3000	370	200	230	45	Prism.
429221	36	3200	3000	370	200	230	45	Prism.
429228	40	3900	3000	550	400	400	45	Prism.
429213	14	1100	3000	190	120	140	41	Opal
429225	22	1700	3000	190	120	140	41	Opal
429214	28	2400	3000	370	200	230	45	Opal
429220	36	3000	3000	370	200	230	45	Opal.
429229	40	3600	3000	550	400	400	45	Opal.

Ca. 15% lavere lumen med CRI 90



Armaturen skal aldri tilkobles byggestrøm.
Armaturen skal primært megges med 250V DC.
Hvis det benyttes 500V må fasene sammenkobles.